

Physical Properties:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Backing: Osnaburg

All patterns are stocked in 30 lineal yard bolts.

Federal Specifications:

Cali™ as manufactured by Colour & Design Inc. meets or exceeds G.S.A. Federal Specification CCC-W-408A through D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This product has been accepted for use by the City of New York Department of Building.

In addition, this product meets Type II CCC-W-408A through D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

Fire Hazard Classification Results:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 15

Smoke Developed 25

Flame Spread

Fire Propagation

Class 1

Class 0

Anti-Microbial Features:

Vinyl wallcoverings contain bactericides and mildew inhibitors to protect the products from microbiological and mildew growth.

5 Year Warranty Against Manufacturing Defects:

Use only adhesives and primers as recommended by the manufacturer.

Environmental Statement:

We are dedicated to complying with today's environmental issues, and have eliminated all heavy metals such as lead, mercury, cadmium and chromium from our inks and adhesives.

NOTE: The assigned numerical rating and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

INSTALLATION NOTE

Cali™ is a random match / reversible pattern.