

Physical Properties:

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 21 oz./lin. yard (619 G/PLM)
14 oz./sq. yard (451 G/PSM)

Backing: Osnaburg

All patterns are stocked in 30 lineal yard bolts and must be ordered in 15 yard increments.

Federal Specifications:

Lavina Silk™ as manufactured by Colour & Design Inc. meets or exceeds G.S.A. Federal Specification CCC-W-408A through D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This product has been accepted for use by the City of New York Department of Building MEA-381-93M.

In addition, this product meets Type II CCC-W-408A through D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

Fire Hazard Classification Results:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 5

Smoke Developed 15

Flame Spread

Fire Propagation

Class 1

Class 0

Anti-Microbial Features:

Vinyl wallcoverings contain bactericides and mildew inhibitors to protect the products from microbiological and mildew growth.

5 Years Warranty Against Manufacturing Defects:

Use only adhesives and primers as recommended by the manufacturer.

Environmental Statement:

Environmentally benign water-based inks used exclusively.

We are dedicated to complying with today's environmental issues, and have eliminated all heavy metals such as lead, mercury, cadmium and chromium from our inks and adhesives.

NOTE: The assigned numerical rating and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

INSTALLATION NOTE

Lavina Silk™ is a random match / reversible pattern.

Design and Materials
Copyright © 2004 colour & design inc.
All Rights Reserved

MADE IN USA



TEL: 501-372-3550
FAX: 501-372-3553
www.colouranddesign.com