
Physical Properties:

54" (137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin. yard (619 G/PLM)

13.3 oz./sq. yard (451 G/PSM)

Backing: Osnaburg

All patterns are stocked in 30 lineal yard bolts.

Federal Specifications:

Miko Block™ as manufactured by Colour & Design Inc. meets or exceeds G.S.A. Federal Specification CCC-W-408D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This product has been accepted for use by the City of New York Department of Building MEA-205-90M.

In addition, meets Type II CCC-W-408D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

Fire Hazard Classification Results:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 15

Smoke Developed 25

Flame Spread

Fire Propagation

Class 1

Class 0

Anti-Microbial Features:

Colour & Design Inc. wallcoverings shall contain anti-microbial additives to resist the growth of mildew and bacteria, including staphylococcus aureus, streptovercillum reticulum (pink stain) and mixed fungal spore such as aspergillus niger, chaetomium globosum, and penicillum funiculosum.

5 Year Warranty Against Manufacturing Defects:

Use only adhesives and primers as recommended by the manufacturer.

Environmental Statement:

We are dedicated to complying with today's environmental issues, and have eliminated all heavy metals such as lead, mercury, cadmium and chromium from our inks and adhesives.

NOTE: The assigned numerical rating and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

INSTALLATION NOTE

Miko Block™ is a random match / reversible pattern.