

**PHYSICAL PROPERTIES:**

52"/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 21 oz./lin. yard (651 G/PLM)

14 oz./sq. yard (474 G/PSM)

Backing: Non-Woven

All patterns are stocked in 30 lineal yard bolts and must be ordered in 15 yard increments.

**FIRE HAZARD CLASSIFICATION RESULTS:**

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 10

Smoke Developed 10

In addition, this product meets Type II CCC-W-408A through D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance

**ENVIRONMENT & HEALTH:**

Meets California Section 01350 IAQ test requirements for wallcovering

Can contribute to LEED® EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives

Can contribute to LEED® MR 5.1 point for regional materials

All installations must conform to Colour & Design's current Hanging Instructions and Product Technical information.

**ANTI-MICROBIAL FEATURES:**

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

**BREATHE FREE™ MICRO-VENTING AVAILABLE UPON REQUEST:**

Breathe Free™ Micro-vented wallcovering from Colour & Design can be used to help control un-wanted moisture inside a building envelope.

**LIMITED WARRANTY:**

5 year warranty against manufacturing defects. Additional information is available at [www.colouranddesign.com](http://www.colouranddesign.com)

**INSTALLATION NOTE**

Quill™ is a straight across match / non reversible pattern.  
For hanging instructions go to: [www.colouranddesign.com](http://www.colouranddesign.com)